



# PRODUCT DATA SHEET

## D2526 - Double-Coated PVC Tape



### Description:

Use this white PVC film with double-sided acrylic tape, that's great for bonding to nearly all materials. It has excellent temperature, UV and water vapor resistance. This gold siliconized paper liner is most commonly used in the awards and sign industry. This tape offers cushioning, protection, and stabilization for all packaging applications.

➤ **Great choice for permanent bonding to metals and painted or varnished surfaces.**

### Features:

- Aggressive acrylic adhesive
- Great bond to nearly all materials
- Excellent temperature, UV and water vapor resistance



Assembly	Bonding
Masking	Splicing

Product Data			
<b>Carrier</b>	PVC	2.0 mil	0.05 mm
<b>Adhesive (both sides)</b>	Acrylic	3.0 mil	0.08 mm
<b>Liner</b>	Yellow Glassine Paper	3.0 mil	.08 mm
<b>Total Tape Thickness</b>	Excluding Liner	8.0 mil	0.2 mm
<b>Peel Adhesion</b>	From Stainless Steel	88 oz/in	24 N/25 mm
<b>Loop Tack</b>	From Stainless Steel	TBD	TBD
<b>Temperature Resistance</b>	-	-22°F to 194°F	-30°C to 90C

### Application Notes:

Excellent choice for permanent bonding to metals, painted or varnished surfaces. Very commonly used in the awards and sign industry. Also used as a hold-down tape in composite machining applications.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

Good	Better	Best	Not Recommended
------	--------	------	-----------------