



PRODUCT DATA SHEET

DK - Non-Adhesive Vinyl

Description:

This yellow vinyl adheres to itself, conforms to curves, corners, and hard to reach areas, by forming a leak proof bond. Use this vinyl when you want to mask off areas for plating, painting, or abrasive blasting. It will not create a residue on most surfaces and it is hand-tearable.

↪ This is an engineering grade plating tape and can be suitable for painting.

Features:

- High elongation and good strength
- Easy unwind and good “cling” characteristics
- Highly economical for masking large areas quickly



Product Data			
Baking	Poly Vinyl Chloride PVC	4 mil	.10
Adhesive	None	0	0
Total Tape Thickness	-	4 mil	.10 mm
Temperature Range	-	15°F to 200°F	-9°C to 121°C
Color	-	Yellow	

Assembly	Bonding
Masking	Splicing

Application Notes:

Provides great conformability and superior masking in hard chrome and other plating applications. Could also be used for packaging, tying, and binding.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

Good	Better	Best	Not Recommended
------	--------	------	-----------------