



PRODUCT DATA SHEET

S192- Self Wound Vinyl Tape

Description:

Plasticized PVC film with a rubber-based adhesive in OSHA colors. For cable coding, quick identification of electrical phases, circuits, feeders and branches.

Features:

- Conformable vinyl backing
- Completely masks off areas
- Chemically and temperature resistant
- Withstands treatment baths
- Economical size roll
- UL/CSA/CE listed inside core
- Saves time and money



| Product Data | | | |
|-------------------------------|-----------------------|----------|-----------|
| Carrier | Plasticized PVC Vinyl | | |
| Adhesive | Rubber Based | | |
| Total Tape Thickness | - | 7.0 mils | .177 mm |
| Peel Adhesion | From Stainless Steel | 23 oz/in | 6 N/25 mm |
| Tensile | | 16lb/in | 3N/25mm |
| Elongation | | 200% | |
| Temperature Resistance | | 176°F | 80°C |

| | |
|----------|----------|
| Assembly | Bonding |
| Masking | Splicing |

Application Notes:

Nickel plating and anodizing mask off. Wire and cable harnessing. Electrical insulation up to 600 volts and 80°C/176°F.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

| | | | |
|------|--------|------|-----------------|
| Good | Better | Best | Not Recommended |
|------|--------|------|-----------------|