



PRODUCT DATA SHEET

S201- Self-Wound PVC

Description:

35-micron UPVC film. High tack rubber adhesive system provides immediate adhesion to papers, film and variety of surfaces. Excellent for butt splicing, sealing, seaming, block-out for screen printers and for color coding. Ideal printing surface for a broad range of packaging and identification purpose.

Similar to 3M 690

Features:

- Conformable film seals, seams irregular shapes
- Colors are easily identifiable
- Imprintable and heat shrinkable
- Aggressive adhesive for fast application
- Wide temperature range for a variety of applications



Product Data			
Carrier	Unplasticized PVC Vinyl	1.5 mils	.038 mm
Adhesive	Natural Rubber	1.mil	.025 mm
Total Tape Thickness	-	2.5 mils	.063 mm
Peel Adhesion	From Stainless Steel	15 oz/in	4N/25 mm
Tensile		42lbs/in	7N/25mm
Elongation		75%	
Service Temperature	-40°F to 150°F	-40°C to 54°C	
Colors	Black, White, Red, Dark Blue, Light Blue, dark Green, Light Green, Orange & Yellow		

Assembly	Bonding
Masking	Splicing

Application Notes:

Seaming insulation material, Styrofoam, cardboard and poly films. Imprinted box sealing tape, color coding, splicing low energy surfaces such as polyethylene and block-out tape for screen printing.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

Good	Better	Best	Not Recommended
------	--------	------	-----------------