



PRODUCT DATASHEET

S293YL - Yellow PET Silicone Splicing Tape



Description:

The most common application for this tape is for splicing siliconized release liner. It is also useful for splicing raw films exposed to high-temperature processes. This is a reliable and effective silicone splicing tape both by hand and at high speed. It effectively bonds to low surface energy materials, with high tack, high shear strength, and high temperature resistance. This product has a soft splicing adhesive with a conformable 1 mil PET backing.

Features:

- Soft, high-tack silicone splicing adhesive
- Conformable 1.0 mil PET backing allows for complete surface contact
- Solvent and chemical resistance
- High temperature stability



Product Data			
Carrier	Polyester	1.0 mil	0.02 mm
Adhesive	Silicone	2.5 mil	0.06 mm
Total Tape Thickness	-	3.5 mil	0.08 mm
Peel Adhesion	From Stainless Steel	35 oz/in	9 N/25 mm
Loop Tack	From Stainless Steel	50 oz/in	13 N/25 mm
Temperature Resistance	-	400°F	205°C

Assembly	Bonding
Masking	Splicing

Application Notes:

The most common application is for splicing siliconized release liner. Also useful for splicing raw films when they will be exposed to high temperatures.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

Good	Better	Best	Not Recommended
------	--------	------	-----------------