



# PRODUCT DATASHEET

## S998GR - Ultra High Tack Green Silicone Tape

### Description:

This tape features a soft, ultra-high-tack silicone adhesive, which provides excellent quick stick characteristics to silicone release liners. It also makes for an excellent choice for splicing situations that demand a strong initial stick.

### Features:

- Excellent performance in elevated temperatures
- Clean removal from most surfaces
- Use for splicing of silicone coated paper and films
- Excellent tensile strength



Product Data			
Carrier	Polyester	1.5 mil	.038 mm
Adhesive	Silicone	1.6 mil	.041 mm
Total Tape Thickness	-	3.1 mil	.079 mm
Peel Adhesion	From Stainless Steel	42 oz/in	11 N/25 mm
Loop Tack	From Stainless Steel	42 oz/in	11 N/25 mm
Temperature Resistance		400°F	204°C
Color	Green		

Assembly

Bonding

Masking

Splicing

### Application Notes:

Commonly used in high temperature splicing and surface protection, along with quick stick and increased adhesion levels.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

Good

Better

Best

Not Recommended