



# PRODUCT DATASHEET

## D7502-ULTI-MATT PREMIUM ATG Tape

### Description:

A great, high performance transfer tape for double matting and mounting. Also, ideal for sealing dust covers. The adhesive will not dry out or deteriorate with age and it is quick and easy to use. This high performance transfer tape can be used on a wide variety of materials.

### Features:

- Permanently bonds to paper, plastics and films
- Useful as a core start-up tape
- Acid free for archival projects



Product Data			
<b>Backing</b>	None		
<b>Adhesive</b>	Acrylic/reinforced fibers		
<b>Liner</b>	Yellow Glassine Paper	3.0 mils	0.08 mm
<b>Total Tape Thickness</b>	Excluding liner	1.5 mils	0.04 mm
<b>Peel Adhesion</b>	From Stainless Steel	54 oz/in	15 N/25 mm
<b>Temperature Resistance</b>	-	250°F	121°C
<b>Color</b>	Clear		

Framing	Awards
Signs	Trophies

### Application Notes:

Most commonly used in framing and mounting applications for setting mats and securing pictures in frames. Also very useful in automated applications like core start-up and assembly of point-of-purchase (P.O.P.) displays.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

Good	Better	Best	Not Recommended
------	--------	------	-----------------

800-545-8273 • 262-835-0748 • Fax: 262-835-0749 • [www.specialtytapes.net](http://www.specialtytapes.net)  
4221 Courtney Road • Franksville, WI 53126