



# PRODUCT DATASHEET

## FMCS2-55- FASTSIGN Packing Tape

### Description:

FASTSIGNS Customized Carton Sealing Tape

### Feature

- Custom branded logo
- Easily identifiable

Product Data			
<b>Carrier</b>	Polyester	1.0 mil	0.03 mm
<b>Adhesive</b>	Water Based Acrylic	1.0 mil	0.03 mm
<b>Total Tape Thickness</b>	-	2.0 mils	0.05 mm
<b>Peel Adhesion</b>	From Stainless Steel	35 oz/in	9.8 N/25 mm
<b>Temperature Resistance</b>	-	80° F	26° C
<b>Color</b>	White		

Packing	Bonding
Masking	Splicing

### Application Notes:

Great for packaging, BOPP packing tape; BOPP film coated with water based acrylic glue.

To achieve ultimate adhesion, the bonding surface should be dry, clean, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

Good	Better	Best	Not Recommended
------	--------	------	-----------------

800-545-8273 • 262-835-0748 • Fax: 262-835-0749 • [www.specialtytapes.net](http://www.specialtytapes.net)  
4221 Courtney Road • Franksville, WI 53126